



Technical Data Sheet

EUDUAL 15W-40

Mineral lubricant for all types of vehicles

EUDUAL 15W-40 presents an additivation developed to obtain maximum efficiency in terms of detergency. Its use allows protection of conventional engines by the formation of sludge, control and prevention of wear phenomena.

Applications & Benefits

- Noise Reduction

Use of the product reduces the vibration and noise of the engine. The guide is more fluid and silent.

- One-Technology

The additives used allow the lubricant to be used in petrol, diesel and gas engines.

- High quality bases oils

The raw refining bases, used, reduce volatility by allowing lower consumption of lubricant and significantly reduce filling.

- Oxydation stability

It keeps the car's performance constant over time until the next oil change, as it resists the oxidative degradation phenomena.

Specifications & Approvals

- Exceeds the specifications listed below:

SAE 15W/40

API SJ/CF



OLI MOTORE AUTO
CAR MOTOR OILS

* For further information please contact the Technical Service.



Chemical-Physical Characteristics

| Tests | Method | EUDUAL 15W-40 |
|--|-------------|---------------|
| SAE Grade | - | 15W-40 |
| Density @ 15°C, Kg/dm ³ | ASTM D 4052 | 0.880 |
| Viscosity cSt @ 40°C cSt @ 100°C | ASTM D 445 | 105.0 13.7 |
| Viscosity Index - Unit | ASTM D 2270 | 132 |
| Flash Point °C | ASTM D 92 | 230 |
| Pour Point °C | ASTM D 4052 | - 30 |

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

Storage, Health & Environment

- Storage & Health

It is recommended to store the EUDUAL 15W-40 Lubricant under cover. If storage is carried out outdoors, it is recommended to position the drums, preferably under a roof, in a horizontal position and, if kept upright, cover them with a lid to prevent water infiltration. It is advisable not to store the packs at temperatures above 60 ° C or directly to the sun as it is good to keep them in places not subject to freezing.

EUDUAL 15W-40 has no health effects when properly used, applying the standard personal hygiene standards.

- Environment

Do not discharge the new and/or exhausted lubricant into the sewage system, soil or watercourses. Exhausted lubricant must be delivered to an authorized collection point.

Additional information

- Safety Data Sheet

It is provided aside and must be considered for its information or can be easily downloaded from www.rilub.it

Contact your technical service for more information:



+390813383413



luigi.vassallo@rilub.it