



Technical Data Sheet

EULOGORI

Mineral multigrade lubricant for vintage engines

Provides reliable protection for older engines that have high mileage, helping to prevent the formation of sludge and reducing wear phenomena. The improved formula allows its use where required specifications API SJ/CF.

Applications & Benefits

- Cleaness Technology

It guarantees a better degree of cleaning than conventional mineral-based lubricants. It protects against the formation of lacquers and bumps that are extremely damaging to the engine.

- Wear Protection

The additives create a thin film between the moving mechanical components protecting them from wear and tear.

- Viscosity

High viscosity reduces leakage even in engines with high mileage, reducing lubricant consumption.

- One-Technology

The additives used allow the lubricant to be used in petrol, diesel and gas engines.

- Additional Grade

On some occasions, the classic gradation SAE 20W-50 may be insufficient against the drawing phenomena; The SAE 20W-60 gradation (green color) can be used for this purpose.

Specifiche & Approvazioni

- Exceeds the specifications listed below:

SAE 20W-50 & SAE 20W-60

API SJ/CF

* For further information please contact the Technical Service.



Chemical-Physical Characteristics

Test	Method	EULOGORI	
		20W-50	20W-60
<i>Gradazione SAE</i>	-	<i>20W-50</i>	<i>20W-60</i>
SAE Grade	-	Ambra	Verde
Density @ 15°C, Kg/dm ³	ASTM D 4052	0.880	0.880
Viscosity cSt @ 40°C cSt @ 100°C	ASTM D 445	154.5 18.5	196.0 22.0
Viscosity Index - Unit	ASTM D 2270	132	132
Flash Point °C	ASTM D 92	230	230
Pour Point °C	ASTM D 4052	- 30	-27

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

Storage, Health & Environment

- Storage & Health

It is recommended storing the EULOGORI Lubricant under cover. If storage is carried out outdoors, it is recommended to position the drums, preferably under a roof, in a horizontal position and, if kept upright, cover them with a lid to prevent water infiltration. It is advisable not to store the packs at temperatures above 60 ° C or directly to the sun as it is good to keep them in places not subject to freezing.

EULOGORI has no health effects when properly used, applying the standard personal hygiene standards.

- Environment

Do not discharge the new and / or exhausted lubricant into the sewage system, soil or watercourses. Exhausted lubricant must be delivered to an authorized collection point.

Additional information

- Safety Data Sheet

It is provided aside and must be considered for its information or can be easily downloaded from www.rilub.it

Contact your technical service for more information:



+390813383413



luigi.vassallo@rilub.it