



## Technical Data Sheet

# EUMIX 2T

## 2 Stroke lubricant for motorcycles

High quality lubricant for 2-stroke engines that combines excellent cleaning and high engine protection, also determines a reliable control of residues from the combustion with significant reduction of smokiness. EUMIX 2T is suitable both for those motorcycles equipped with oil injection systems than for those in the pre-mixing.

### Applications & Benefits

#### - Reliable Performance

It limits the formation of combustion and discharge tanks, maintaining engine performance unchanged.

#### - Advanced Protection

Specially engineered formulation for the 2-stroke engine head, in order to prevent and reduce the formation of deposits.

#### - Low Smoke

The presence in the formulation of dedicated, well-balanced dedicated additives reduces exhaust fumes, thus limiting the environmental impact.

#### - Mixing Properties

EUMIX 2T can be used in both injection systems mounted on modern 2-stroke engines and in pre-mixing systems.

#### - Main Application

The lubricant has been developed to offer maximum performance for two-stroke engines both injecting and pre-mixing. EUMIX 2T should not be used in outboard motors. For these applications the use of marine products is recommended.

### Specifications & Approvals

#### - Exceeds the specifications listed below:

API TC

JASO FB

ISO-L-EGB



\* for further information please contact the Technical Service.



## Chemical-Physical Characteristics

Test	Method	EUMIX 2T
Denisty @ 15°C, Kg/dm <sup>3</sup>	ASTM D 4052	0.872
Viscosity cSt @ 40°C cSt @ 100°C	ASTM D 445	63.1 8.9
Viscosity Inex - Unità	ASTM D 2270	115
Flash Point °C	ASTM D 92	220
Pour Point °C	ASTM D 4052	-24

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

## Storage, Health & Environment

### - Storage & Health

It is recommended to store the EUMIX 2T Lubricant under cover. If storage is carried out outdoors, it is recommended to position the drums, preferably under a roof, in a horizontal position and, if kept upright, cover them with a lid to prevent water infiltration. It is advisable not to store the packs at temperatures above 60 ° C or directly to the sun as it is good to keep them in places not subject to freezing.

EUMIX 2T has no health effects when properly used, applying the standard personal hygiene standards.

### - Environment

Do not discharge the new and/or exhausted lubricant into the sewage system, soil or watercourses. Exhausted lubricant must be delivered to an authorized collection point.

## Additional information

### - Safety Data Sheet

It is provided aside and must be considered for its information or can be easily downloaded from [www.rilub.it](http://www.rilub.it)  
Contact your technical service for more information:



+390813383413



[luigi.vassallo@rilub.it](mailto:luigi.vassallo@rilub.it)