

HYDRAULIC H.V.I.

Hydraulic lubricant for systems subject to significant changes in temperature

Hydraulic Fluids special technology to ensure high security and performance that meet the widest range of hydraulic applications in the most diverse conditions of thermal stress. They have a strong resistance to thermal-oxidative degradation arising from environmental and operational variations in temperature, improving the protection against the formation of deposits which tend to decrease the efficiency of hydraulic power transfer systems.

Applications & Benefits

- Low maintenance costs

Extended extended gear change compared to conventional hydraulics, as it has a higher resistance to thermal and chemical degradation. Minimizes squeegee formation, ensuring improved reliability and cleanliness of the hydraulic system.

- Advanced protection

The proven action of additives reduces the wear and corrosive effects affecting the metal parts, making it usable in a wide range of operating conditions, including low loads and heavy loads.

- Thermal degradation resistance

Highly refined bases with the help of additives allow the lubricant to withstand thermal and chemical degradation, thus reducing the formation of sludge.

- Demulsivity

Demulsive capacity to avoid formation of stable oil mixtures with water that may be accidentally present in the hydraulic circuits and hence obstructing the degradation of the oil.

- Foam performance

Easy release of absorbed air and limited foaming, thus avoiding the inappropriate operation of the power transmission device.

- Versatility

Hydraulic H.V.I. Is recommended for use in a wide range of hydraulic applications in industrial and production environments, in mobile hydraulic applications such as excavators, cranes, and precision hydraulic systems that require excellent lubricant fluidity control at temperature variations, including Applications where there are significant environmental and operational thermal excursions and marine applications where ISO HV fluids are required.

Specifications & Approvals

- Exceeds the specifications listed below:

Hydraulic Oil **HYDRAULIC H.V.I.** Are classified **ISO-L-HV** according to **ISO 6743-4**

DIN 51524-Part3 (Classe HVLP)

Cincinnati Lamb P68-P69-P70

EATON-VICKERS M-2950-S

U.S. STEEL 127

DENISON HF1-HF2-HF0

AFNOR NFE 48-690/691

GM LH-03/ LH-04/LH-06

ASTM 6158-05 (HV)





Remember to always check the usage and maintenance manual for the correct choice.
Hydraulic Fluids HYDRAULIC H.V.I. Are compatible with all mineral based lubricants, however i

Hydraulic fluids should never be mixed with others (such as biodegradable, flame retardants, etc.).
* For further information please contact the Technical Service.

Chemical-Physical Characteristics

| Test | Method | HYDRAULIC H.V.I. | | | | |
|------------------------------------|-------------|------------------|-----------|-----------|------------|------------|
| | | 32 | 46 | 68 | 100 | 150 |
| ISO Grade | - | 32 | 46 | 68 | 100 | 150 |
| Density @ 15°C, Kg/dm ³ | ASTM D 4052 | 0.870 | 0.875 | 0.880 | 0.885 | 0.885 |
| Viscosity | | | | | | |
| cSt @ 40°C | ASTM D 445 | 32.0 | 46.0 | 68.0 | 100.0 | 150.0 |
| cSt @ 100°C | | 6.2 | 7.9 | 10.5 | 14.0 | 18.8 |
| Viscosity Index | ASTM D 2270 | 142 | 142 | 142 | 142 | 142 |
| Copper Corrosion – 3h a 100°C | ASTM D 130 | 1A | 1A | 1A | 1A | 1A |
| Anti-rust Properties | ASTM D 665A | Pass | Pass | Pass | Pass | Pass |
| Pour Point, °C | ASTM D 97 | -36 | -36 | -33 | -33 | -30 |
| Flash Point, °C | ASTM D 93 | 222 | 226 | 235 | 230 | 230 |
| Demulsivity, minutes 40/40/0 | ASTM D 1401 | 5 | 5 | 5 | 5 | 5 |
| Foam | | | | | | |
| Trend / Stability | ASTM D 892 | 0/0 | 0/0 | 0/0 | 0/0 | 0/0 |
| FZG / esceed stadium | DIN 51354 | 12 | 12 | 12 | 12 | 12 |

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

Storage, Health & Environment

- Storage & Health

It is recommended to store HYDRAULIC H.V.I. Lubricant inside. If storage is carried out outdoors, it is recommended to position the drums, preferably under a roof, in a horizontal position and, if kept upright, cover them with a lid to prevent water infiltration. It is advisable not to store the packs at temperatures above 60 ° C or directly to the sun as it is good to keep them in places not subject to freezing.

HYDRAULIC H.V.I. Does not have any health effects when properly used, applying the normal personal hygiene standards.

- Environment

Do not discharge the new and / or exhausted lubricant into the sewage system, soil or watercourses. Exhausted lubricant must be delivered to an authorized collection point.



Additional information

- Safety Data Sheet

It is provided aside and must be considered for its information or can be easily downloaded from www.rilub.it

Contact your technical service for more information:



+390813383413



luigi.vassallo@rilub.it