



Technical Data Sheet

M.G.V. 0W-30 FJ

FULL SYNTHETIC LUBRICANT FOR FORD AND JAGUAR LAND ROVER CARS

High performance full synthetic lubricant designed to be used in the latest generation engines, recommended in Ford vehicle engines that require an oil that meets the WSS-M2C950-A specification, it can be also used in Jaguar and Land Rover cars thanks to the satisfaction of STJLR 03.5007 specification requirements ('Ingenium' latest generation Diesel engines). Furthermore, the product is suitable for use in petrol and diesel engines in which the manufacturer requires a lubricant that complies with the Fiat 9.55535-GS1 and Fiat 9.55535-DS1 specifications.

Applications & Benefits

- Emission control protection

The SAE 0W-30 grade allows to obtain significant benefits in terms of Fuel Economy with the consequent reduction of CO2 emissions.

- Formulation

The use of POLYALFAOLEFINE (PAO) guarantees low volatility of the lubricant, lower consumption and therefore topping up.

- Engine Protection

Offers exceptional protection in all driving conditions, reducing the formation of deposits.

- MID SAPS

Thanks to the particular Mid SAPS additives, the product is compatible with the latest exhaust gas post-treatment systems.

Specifications

- Meets specification as follows:

SAE 0W-30

ACEA C2

FORD WSS-M2C950-A

JAGUAR LAND ROVER JLR.03.5007

RECOMENDATIONS

Fiat 9.55535-GS1 e Fiat 9.55535-DS1

* for further information please contact the Technical Service.



Chemical-Physical Characteristics

Test	Method	M.G.V. 0W-30 FJ
SAE	-	0W-30
Density @ 15°C, Kg/dm ³	ASTM D 4052	0.850
Viscosity cSt @ 40°C cSt @ 100°C	ASTM D 445	51.0 9.5
Viscosity Index - Unità	ASTM D 2270	180
Flash Point °C	ASTM D 92	225
Pour Point °C	ASTM D 4052	- 45

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

- Storage, Health & Environment

Storage & Health

It is recommended to store the M.G.V. 0W-30 FJ indoor. If storage is required outdoors, it is recommended to place the drums, possibly under a canopy, in a horizontal position and, if kept in a vertical position, cover them with a lid to prevent water infiltration. It is advisable not to store the packaging at temperatures above 60 ° C or directly in the sun as well as to keep them in places not subject to frost.

M.G.V. 0W-30 FJ has no health effects when used correctly, applying normal personal hygiene standards.

Environment

Do not discharge new and / or exhausted lubricant into the sewer system, into the ground or into waterways. The used lubricant must be delivered to an authorized collection point.

Additional details

- Safety Data Sheet

It is provided separately and must be considered for the related information or can be easily downloaded from the website www.rilub.it

For further information contact the technical service:



+390813383413



infolab@rilub.it