



## Technical Data Sheet

# M.G.V. Race Performance 10W-60

## *Born for Competitions*

M.G.V. RACE PERFORMANCE 10W-60 is a Fully Synthetic lubricant developed to meet the special requirements of all those cars equipped with high-performance engines and where required specific API SN and/or ACEA A3/B4.

### Applications & Benefits

#### - Active Formula

Provides continuous protection to the engine of dirt and sludge formation.

#### - Synthetic bases

The nature of the bases used ensures low volatility of the lubricant, less fuel consumption and therefore dribbles.

#### - Wear Protection

The nature of the additives gives the preparation more resistance to oxidative phenomena that tend to degrade the lubricant. As a result, maximum engine protection is guaranteed.

#### - One -Technology

The additives used allow the lubricant to be used in petrol, diesel and gas engines.

#### - Low Evaporation

The synthetic bases used have a high degree of evaporation stability, which results in improved lubricity stability and a significant reduction in the frequency of filling.

#### - Race Formula

It is well known that competitive motors are subject to stresses that could result in excessive wear and tear. The formulation guarantees exceptional protection even in extreme operating conditions.


### Specifications & Approvals

#### - Exceeds the specifications listed below:

SAE 10W-60

API SN/CF

ACEA A3/B3 – A3/B4



OLI MOTORE AUTO  
CAR MOTOR OILS

\*For further information please contact the Technical Service.



## Chemical-Physical Characteristics

Test	Method	M.G.V. Race Performance 10W-60
<b>SAE Grade</b>	-	<b>10W-60</b>
Density @ 15°C, Kg/dm <sup>3</sup>	ASTM D 4052	0.855
Viscosity cSt @ 40°C cSt @ 100°C	ASTM D 445	150.0 22.5
Viscosity Index - Unit	ASTM D 2270	178
Flash Point °C	ASTM D 92	220
Pour Point °C	ASTM D 4052	- 39

NOTE: The above values are "typical" for normal production tolerance and do NOT constitute a specification.

## Storage, Health & Environment

### - Storage & Health

It is recommended to store the M.G.V. Race Performance 10W-60 Lubricant under cover. If storage is carried out outdoors, it is recommended to position the drums, preferably under a roof, in a horizontal position and, if kept upright, cover them with a lid to prevent water infiltration. It is advisable not to store the packs at temperatures above 60 ° C or directly to the sun as it is good to keep them in places not subject to freezing.

M.G.V. Race Performance 10W-60 has no health effects when properly used, applying the standard personal hygiene standards.

### - Environment

Do not discharge the new and/or exhausted lubricant into the sewage system, soil or watercourses. Exhausted lubricant must be delivered to an authorized collection point.

## Additional information

### - Safety Data Sheet

It is provided aside and must be considered for its information or can be easily downloaded from [www.rilub.it](http://www.rilub.it)

Contact your technical service for more information:



+390813383413



[luigi.vassallo@rilub.it](mailto:luigi.vassallo@rilub.it)